


**MORE**  
**COMFORT**  
**SPEED**  
**PRECISION**  
**REACH**



Cushion handle:  
less vibration

**Primact**  
striking module inside

Light impact all-around  
striking cap

Short casting for  
closer end-wall reach

**LoadXtend** (L/S)

Bi-direction  
adjustable base

3/4" (19mm) factory set  
Adjustable for 5/8" to 7/8" (16 to 22mm)



**Primact**  
Powered  
Enduring Service  
**1.25M**  
cycle valve



\* Also available in stainless steel



\* Also available in stainless steel



**Weight :** 11 lbs (5kg)  
**Height :** 17 3/4" (451mm)  
**Length :** 15" (327 mm)  
**Width :** 5.2" (141mm)

#### Capacity

- 100 **T** nails
- 200 **L** nails LoadXtend
- 138 Staples LoadXtend

#### Operating pressure

80-110 psi (5,5 -7,6 bar)

#### Lubrication

A few drops of  
a non-detergent oil weekly

#### Air coupler required

3/8" (9,65mm) NPT

#### Warranty

7 years on cast  
1 year on parts  
(excluding wear parts)

#### Factory set

3/4" (19mm) flooring

#### Applications

5/8" to 7/8" (16 to 22mm)

#### Wood

Solid and Engineered  
Domestic or Exotic

#### Optional accessories

- 3" (76mm) rotating extension handle (A800)
- **LoadXtend** 300 16ga L type nail channel (P249A)
- **PrimSurfer** roller base add-on kit (A 861)

