

Top 360°  
air deflector

## 15ga Finish Nailer

For first and last rows  
of hardwood flooring

Lightweight die-casting  
magnesium body

Adjustable depth control


Quick clear  
jam release

No mar rubber tip device

Anti-dry fire  
mechanism

Adjustment knob for either  
sequential or contact trip fire

Accept 1-1/4" to 2-1/2" (32mm to 64mm)  
15ga 34° collated angle "DA" style finish nails



**Nails DA**

**15ga**

2" / 50mm  
2 1/2" / 64mm

**Weight :** 4 lbs (1,83kg)  
**Height :** 13" (331mm)  
**Length :** 11.9" (302 mm)  
**Width :** 3.9" (100mm)

**Magazine Capacity**  
100 nails

**Operating pressure**  
70 – 120 psi (5 – 8 bar)

**Lubrication**  
5 drops of a non-detergent  
oil daily

**Air consumption @ 100psi**  
0.032  
SCF / cycle

**Noise dBA**  
95.3

**Certification**  
"CE" approved

**Warranty**  
1 year

**Vibration m/sec<sup>2</sup>**  
2.33

**Applications**  
Hardwood flooring, baseboards,  
casings, moldings, paneling, etc.

**Collation angle**  
34 degree



1135, Jérémie-Fortin  
Québec, QC G1J 1R8  
Canada

Tel : 1 (418) 522-7744  
USA / CAN : 1 (800) 363-1962  
UK : +01-418-522 5355  
Fax : 1 (418) 522-7466  
sales@primatech.ca  
www.primatech.ca



\* Illustrations are for reference